

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro Power 10W-40 CV LS 20 Litre

#### Product Description

Pro Power Ultra 10W-40 CV LS is a fully synthetic Low SAPS engine oil designed for use in Euro 4, 5 & 6 engines. Suitable for truck, bus, coach, off highway and agricultural applications. Suitable for use with exhaust gas re-circulation (EGR), selective catalytic reduction (SCR / Adblue) and diesel particulate filters (DPF)

#### Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: E6, E7 & E9

API: CI-4

Cummins: CES 20076 & CES 20077

DAF: Extended Drain

DEUTZ: DQC III-10, DQC III-10 LA & DQC IV-10 LA

Mack: EO-M+ & EO-N

MAN: 3271-1 & 3477

MB: 228.51

MTU Type 3.1

Renault Truck: RGD & RXD

RVI: RLD-2

Volvo: VDS-3



\* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	D260-020	5020618211372

#### Product Benefits

- \* Premium additives to help control soot and sludge levels in the oil
- \* Ideal for use in severe conditions with extended drain intervals
- \* Not suitable for use in petrol engines

#### Product Usage

Use as per the engine manufacturers recommendations.

#### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

**Pro Power**  
**10W-40 CV LS**  
20 Litre

### Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	14.93
Viscosity, CCS	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.87
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	3.9		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			99.93
Density	ASTM D792	@ 15°C			0.859

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*