

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

15W-40

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 15W-40 is a high quality mineral oil designed for use in turbo and non-turbo charged vehicles with petrol and diesel engines.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A3/B3, A3/B4 & E2

API: CF & SL/CH-4

Mack: EO-L

MAN: 271

MB: 228.1 & 229.1

Volvo: VDS

VW: 505.00

MTU Type 1

Product Benefits

- * Manufactured from high quality mineral oils and high performance additives
- * Provides excellent level of engine cleanliness
- * Premium additives control the formation of lacquers and sludge

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A100-001	5020618210009
5 Litre	A100-005	5020618210016
20 Litre	A100-020	5020618210023
199 Litre	A100-199	5020618210030

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

15W-40

1 Litre, 5 Litre, 20 Litre & 199 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.5	<16.3	14.05
Viscosity, CCS	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		10.62
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	
Pour Point	ASTM D97	°C		-25	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			104.34
Density	ASTM D792	@ 15°C			0.889

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*