

TECHNICAL DATA SHEET

Pro Power

5W-30 GM

1 Litre & 5 Litre

Product Description

Pro Power Ultra 5W/30 GM is formulated primarily to meet GM longlife requirements using the most advanced additive technology to produce a fuel efficient engine oil that has excellent high and low temperature performance and exceptional long term anti wear characteristics. Suitable for use in petrol & diesel engines where specified including: Vauxhall, Opel, Mercedes, BMW and Saab

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A3/B4 API: CF & SM/SL BMW: LL-01 & LL-98 GM: LL-A-025 & LL-B-025

MB: 229.5

XPERTS IN HIGH QUALITY OIL

VW: 505.00 & 502.00



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A474-001	5020618210887
5 Litre	A474-005	5020618210894

Product Benefits

- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Rapid circulation from cold start up

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power

5W-30 GM

1 Litre & 5 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	12.3
Viscosity, CCS	ASTM D4684	mPa.s		<6600	
Total Base Number	ASTM D2896	mg KOH/g	10		
HTHS Viscosity	ASTM D4683	mPa.s	>3.5		
NOACK Volatility	ASTM D5800	%		10	
Pour Point	ASTM D97	°c		-27	

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024