

TECHNICAL DATA SHEET

Pro Power

10W-40 SS

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 10W-40 SS is a semi synthetic oil designed for use in turbo and non-turbocharged vehicles with petrol and diesel engines

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A3/B3 & A3/B4

API: SL/CF MB: 229.1

EXPERTS IN HIGH QUALITY OIL

VW: 505.00 & 502.00

Product Benefits

- * Manufactured from high quality base oils and high performance additives
- * Provides excellent level of engine cleanliness
- * Premium additives control the formation of lacquers and sludge



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A215-001	5020618210047
5 Litre	A215-005	5020618210054
20 Litre	A215-020	5020618210061
199 Litre	A215-199	5020618210078

Product Usage

Use as per the engine manufacturers recommendations,

Storage Instructions

Store upright & sealed in a cool dry place & out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power

10W-40 SS

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	12.5	<16.3	13.46
Viscosity, CCS	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.25
Pour Point	ASTM D97	°c		-35	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			81.77
Density	ASTM D792	@ 15°c			0.872
Viscosity Index	ASTM D2270				160.96

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024