

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

### Pro Power

#### 0W-30 C2 FD

1 Litre, 5 Litre, 20 Litre & 199 Litre

#### Product Description

Pro Power Ultra 0W-30 C2 FD is a fully synthetic, low SAPS, fuel efficient motor oil suitable for use in diesel engines. It is designed to give maximum protection to diesel particulate filters (DPF). Recommended for many modern vehicles, including those from Ford with EcoBlue Diesel engines.

#### Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C2

Fiat: 9.55535-DS1 & 9.55535-GS1

Ford: WSS-M2C950-A

STJLR: .03.5007

BMW: LL-12 FE

#### Product Benefits

- \* Latest synthetic technology motor oil
- \* Formulated to give excellent fuel efficiency
- \* Protects sensitive exhaust after-treatment devices, such as DPF's - diesel particulate filters

#### Product Usage

Use as per engine manufacturers recommendations.

#### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

#### Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A328-001	5020618210207
5 Litre	A328-005	5020618210214
20 Litre	A328-020	5020618210221
199 Litre	A328-199	5020618210238

Revision: 2 | Date: 20/01/2025

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

### Pro Power

#### 0W-30 C2 FD

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.6
Viscosity, CCS	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	7		9.8
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			60.4
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				169

#### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

#### Transport Classification

Please see our latest EC Safety Data Sheets for details.