

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

5W-30 C3 VW

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 5W-30 C3 VW is a fully synthetic, low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engines. It is designed to give maximum protection to diesel particulate filters (DPF). Recommended for many modern vehicles, including those from Audi, VW, Skoda, Seat, BMW, Mercedes-Benz, Porsche and others.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C3
API: SN
BMW: LL-04
MB: 229.51
Porsche: C30
VW: 504.00 & 507.00

Product Benefits

- * Suitable for long life service intervals
- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Protects sensitive exhaust after-treatment devices, such as DPF's - diesel particulate filters

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.



* Image for illustrative purposes only.

| Size | Part No | Barcode |
|-----------|----------|---------------|
| 1 Litre | A331-001 | 5020618210313 |
| 5 Litre | A331-005 | 5020618210320 |
| 20 Litre | A331-020 | 5020618210337 |
| 199 Litre | A331-199 | 5020618210344 |

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

5W-30 C3 VW

1 Litre, 5 Litre, 20 Litre & 199 Litre

Shelf Life

5 Years from date of manufacture.

| | | |
|-------------------------|---|--------------------|
| Appearance | : | Amber liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 12.3 |
| Total Base Number | ASTM D2896 | mg KOH/g | 7 | | 8.33 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.5 | | |
| Viscosity, CCS | ASTM D4684 | mPa.s | | 6600 | |
| Pour Point | ASTM D97 | °C | | -36 | |
| NOACK Volatility | ASTM D5800 | % | | <10 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 76.3 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*