

## **TECHNICAL DATA SHEET**

#### **Pro Power**

## 5W-30 RN17

1 Litre, 5 Litre & 20 Litre

#### **Product Description**

Pro Power Ultra 5W-30 RN17 is a fully synthetic low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engines, designed to give maximum protection to petrol & diesel particulate filters. Recommended for many modern vehicles, including those from Renault and others.

# Recommended for use by Pro Power for the following manufacturer's specifications

MB: 226.52 ACEA: C3 Renault: RN17

EXPERTS IN HIGH QUALITY OIL

#### **Product Benefits**

- \* Latest synthetic technology motor oil
- \* Formulated to give excellent fuel efficiency
- \* Prolong the life of after-treatment systems including catalytic converters and both diesel and petrol particulate filters

\* Image for illustrative purposes only.

Size Part No Barcode

1 Litre A335-001 5020618210443

5 Litre A335-005 5020618210450

20 Litre A335-020 5020618210467



#### **Product Usage**

Use as per engine manufacturers recommendations.

#### **Storage Instructions**

Store sealed and upright in a cool dry place & out of the reach of children.

#### **Shelf Life**

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Revision: 1 | Date: 16/10/2024



## **TECHNICAL DATA SHEET**

### **Pro Power**

## 5W-30 RN17

1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	11.4
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			66
Density	ASTM D792	@ 15°c			0.85
Viscosity, CCS	<b>ASTM D4684</b>	mPa.s		6600	
Total Base Number	<b>ASTM D2896</b>	mg KOH/g	7.5		9.3
HTHS Viscosity	<b>ASTM D4683</b>	mPa.s	>3.5		
NOACK Volatility	ASTM D5800	%		<11	

#### **Safety Precautions**

**EXPERTS IN HIGH QUALITY OIL** 

Please see our latest EC Safety Data Sheets for details.

#### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024