TECHNICAL DATA SHEET

Pro Power

Product Usage

start conditions.

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power

0W-30 LL VW

1 Litre, 5 Litre & 20 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	11.3
Viscosity, CCS	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.21
Pour Point	ASTM D97	°c		-42	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			59.17
Density	ASTM D792	@ 15°c			0.841

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024