

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

Pro Power

**0W-20 ECO VW**

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Pro Power Ultra 0W-20 ECO VW is a fully synthetic low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engine, designed to give reductions in fuel consumption and excellent protection during cold start up. Recommended for many modern vehicles, including those from Audi, VW, Skoda, Seat and Porsche. Please note - this oil is not backwards compatible to VW specifications 504.00/507.00. The oil contains a coloured dye for identification.

### Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C5  
API: SN Plus  
Porsche: C20  
VW: 508.00 & 509.00

### Product Benefits

- \* Latest synthetic technology motor oil, offers engine protection over extended drain intervals
- \* Provides significant reductions in fuel consumption
- \* Exceptional low temperature characteristics meaning that the oil circulates quickly, even in the most demanding cold start conditions

### Product Usage

Use as per engine manufacturers recommendations.

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A355-001	5020618210535
5 Litre	A355-005	5020618210542
20 Litre	A355-020	5020618210559
199 Litre	A355-199	5020618210566

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro Power 0W-20 ECO VW

1 Litre, 5 Litre, 20 Litre & 199 Litre

#### Shelf Life

5 Years from date of manufacture.

Appearance	:	Pale Green Liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	7.8	<9.3	8.7
Viscosity, CCS	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.33
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			42.74
Density	ASTM D792	@ 15°C			0.841

#### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

#### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*