

TECHNICAL DATA SHEET

Pro Power

5W-30 FD

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 5W-30 FD is a fully synthetic oil ideal for use in most Ford vehicles from 2009 onwards. Suitable for turbo and non-turbocharged vehicles with petrol and diesel engines. Recommended for many modern vehicles, including certain Ford vehicles from 2009 onwards.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A1/B1 & A5/B5

API: SL/CF

PERTS IN HIGH QUALITY OIL

Ford: WSS-M2C913-C & WSS-M2C913-D

Renault: RN0700 STJLR: .03.5003

Product Benefits

- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Rapid circulation from cold start up



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A470-001	5020618210726
5 Litre	A470-005	5020618210733
20 Litre	A470-020	5020618210740
199 Litre	A470-199	5020618210757

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power

5W-30 FD

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	10.9
Viscosity, CCS	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°c		-27	
NOACK Volatility	ASTM D5800	%		13	
Total Base Number	ASTM D2896	mg KOH/g	10		12.1
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			61.9
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				169
HTHS Viscosity	ASTM D4683	mPa.s	3	3.5	

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024