

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power 5W-20 ECO FD

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 5W-20 ECO FD is a fully synthetic engine oil formulated for the latest intelligent Eco engines including those with stop/start technology. The carefully selected base stocks and synthetic additives give this multi-grade engine oil high levels of engine component protection as well as being fuel efficient.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C5

API: SN/CF

Chrysler: MS 6395

Ford: WSS-M2C925-B & WSS-M2C948-B

ILSAC: GF-5

STJLR: .03.5004

Product Benefits

- * Premium motor oil recommended for many modern vehicles, including Ford EcoBoost petrol engines
- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Rapid circulation on cold start up

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A471-001	5020618210764
5 Litre	A471-005	5020618210771
20 Litre	A471-020	5020618210788
199 Litre	A471-199	5020618210795

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

5W-20 ECO FD

1 Litre, 5 Litre, 20 Litre & 199 Litre

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.9	<9.3	7.8
Viscosity, CCS	ASTM D4684	mPa.s		6600	4567
Total Base Number	ASTM D2896	mg KOH/g	8		9.795
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		13	11
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			43.523
Viscosity Index	ASTM D2270				150.55
Density	ASTM D792	@ 15°C			0.849
Pour Point	ASTM D97	°C		-35	-39

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*