

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power 0W-20 ECO

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 0W/20 ECO is an advanced fully synthetic low viscosity engine oil formulated for fuel efficiency. It provides excellent wear protection under the most extreme circumstances even at cold start up. This viscosity of oil may not be suitable for use in certain engine types, please refer to the owner manual or handbook.

Recommended for use by Pro Power for the following manufacturer's specifications

API: SN-RC & SP

Chrysler: MS-6395

GM: 4718M, 6094M, Dexos™ 1 Gen 2 & Dexos™ 1 Gen 3

ILSAC: GF-5 & GF-6A

Product Benefits

- * Premium motor oil recommended for many modern petrol and petrol hybrid vehicles
- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Rapid circulation from cold start up



* Image for illustrative purposes only.

| Size | Part No | Barcode |
|-----------|----------|---------------|
| 1 Litre | A473-001 | 5020618210849 |
| 5 Litre | A473-005 | 5020618210856 |
| 20 Litre | A473-020 | 5020618210863 |
| 199 Litre | A473-199 | 5020618210870 |

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

| | | |
|-------------------------|---|--------------------|
| Appearance | : | Amber liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil |

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power 0W-20 ECO

1 Litre, 5 Litre, 20 Litre & 199 Litre

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|----------|------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm²/s | 6.9 | 9.3 | 9 |
| Viscosity, CCS | ASTM D4684 | mPa.s | | 6200 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 8 | | 10.4 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 2.6 | 2.9 | |
| NOACK Volatility | ASTM D5800 | % | | 13 | |
| Density | ASTM D792 | @ 15°C | | | 0.85 |
| Viscosity, Kinematic 40°C | ASTM D445 | mm²/s | | | 49.3 |
| Viscosity Index | ASTM D2270 | | | | 165 |

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*