

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

**Pro Power**

**5W-40**

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Pro power Ultra 5W/40 is a fully synthetic engine oil for today's high performance engines, including multi-valve, fuel injection and turbo charged petrol and diesel engines where specified. This oil is NOT suitable for vehicles that have exhaust after treatment devices fitted.

### Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A3/B3 & A3/B4

API: SN/CF

BMW: LL-98

GM: LL-B-025

MB: 229.3 & 229.5

Porsche: A40

PSA: B71 2296

Renault: RN0700 & RN0710

VW: 505.00 & 502.00



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A475-001	5020618210900
5 Litre	A475-005	5020618210917
20 Litre	A475-020	5020618210924
199 Litre	A475-199	5020618210931

### Product Benefits

- \* Latest synthetic technology motor oil
- \* Formulated to give excellent fuel efficiency
- \* Rapid circulation from cold

### Product Usage

Use as per engine manufacturers recommendations.

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

### Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Revision: 2 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

Pro Power

5W-40

1 Litre, 5 Litre, 20 Litre & 199 Litre

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	13.7
Viscosity, CCS	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	10		12.9
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			80.1
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				176

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 2 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*