

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

**Pro Power**  
**5W-30 DX1**  
1 Litre, 5 Litre & 20 Litre

### Product Description

Pro Power Ultra 5W-30 DX1 is a high performance fully synthetic engine oil that provides protection against low speed pre-ignition (LSPI) issues associated with smaller capacity turbo-charged engines. Suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

### Recommended for use by Pro Power for the following manufacturer's specifications

API: SN Plus, SP & SP RC  
GM: 4718M, 6094M & Dexos™ 1 Gen 2  
Chrysler: MS 6395  
Fiat: 9.55535-CR1  
Honda: HTO-06  
ILSAC: GF-6A  
Opel: OV0401547-G30  
Ford: WSS-M2C946-A



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A480-001	5020618210948
5 Litre	A480-005	5020618210955
20 Litre	A480-020	5020618210962

### Product Benefits

- \* Protects against Low Speed Pre Ignition (LSPI) issues and timing chain wear
- \* Ideal choice in hot running engines where its prevention of deposits keeps turbochargers in optimum condition
- \* Exceptional low temperature characteristics meaning that the oil circulates quickly even in the most demanding cold start conditions

### Product Usage

Use as per engine manufacturers recommendations.

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

**Pro Power**  
**5W-30 DX1**  
1 Litre, 5 Litre & 20 Litre

### Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.37
Viscosity, CCS	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.28
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			61.51
Density	ASTM D792	@ 15°C			0.852

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*