

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro+Power Ultra

5W-30 DX1

1 Litre, 5 Litre & 20 Litre

Product Description

Pro Power Ultra 5W-30 DX1 is a high performance fully synthetic engine oil that provides protection against low speed pre-ignition (LSPI) issues associated with smaller capacity turbo-charged engines. Suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

Recommended for use by Pro Power for the following manufacturer's specifications

API: SN Plus, SP & SP-RC

GM: 4718M, 6094M & Dexos™ 1 Gen 2

Chrysler: MS-6395

Fiat: 9.55535-CR1

Honda: HTO-06

ILSAC: GF-6A

Opel: OV0401547-G30

Ford: WSS-M2C946-A



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A480-001	5020618210948
5 Litre	A480-005	5020618210955
20 Litre	A480-020	5020618210962

Product Benefits

- * Protects against Low Speed Pre Ignition (LSPI) issues and timing chain wear
- * Ideal choice in hot running engines where its prevention of deposits keeps turbochargers in optimum condition
- * Exceptional low temperature characteristics meaning that the oil circulates quickly even in the most demanding cold start conditions

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro+Power Ultra

5W-30 DX1

1 Litre, 5 Litre & 20 Litre

Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.4
Viscosity, CCS	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		10.9
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			63.3
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				145

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*