

## **TECHNICAL DATA SHEET**

#### **Pro Power**

### **HD 75W GL-4**

1 Litre, 5 Litre & 20 Litre

#### **Product Description**

Pro Power Ultra HD 75W GL-4 is a fully synthetic low-viscosity manual transmission fluid that can be used in a wide variety of modern vehicles. Recommended for synchronised manual transmissions where a 75W GL4 gear oil is specified. May be used in certain dry-clutch DCT

systems where a 75W GL4 gear oil is specified.

# Recommended for use by Pro Power for the following manufacturer's specifications

API: GL-4 BMW: MTF LT-3

VW: G 052 178, G 052 512, G 052 726, G 060 726, G 052 527

& G 070 726

PERTS IN HIGH QUALITY OIL

Ford: WSS-M2C200-D2 & M2C200-D3

PSA: 9730.A8



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	B240-001	5020618211112
5 Litre	B240-005	5020618211129
20 Litre	B240-020	5020618211136

#### **Product Benefits**

- \* Latest technology additives ensure positive and problem free gear selection
- \* Exceptionally good high temperature stability ensuring maximum protection

#### **Product Usage**

Use as per vehicle manufacturers recommendations.

#### **Storage Instructions**

Store sealed and upright in a cool dry place & out of the reach of children.

#### **Shelf Life**

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Revision: 1 | Date: 16/10/2024



## **TECHNICAL DATA SHEET**

### **Pro Power**

## **HD 75W GL-4**

1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	7	<11	10.01
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			56.91
Density	ASTM D792	@ 15°c			0.85

#### **Safety Precautions**

**EXPERTS IN HIGH QUALITY OIL** 

Please see our latest EC Safety Data Sheets for details.

#### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024