

PRO+POWER ULTRA

TECHNICAL DATA SHEET

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Pro Power

HD 75W GL-4

1 Litre, 5 Litre & 20 Litre

Product Description

Pro Power Ultra HD 75W GL-4 is a fully synthetic low-viscosity manual transmission fluid that can be used in a wide variety of modern vehicles. Recommended for synchronised manual transmissions where a 75W GL4 gear oil is specified. May be used in certain dry-clutch DCT systems where a 75W GL4 gear oil is specified.

Recommended for use by Pro Power for the following manufacturer's specifications

API: GL-4

BMW: MTF LT-3

VW: G 052 178, G 052 512, G 052 726, G 060 726, G 052 527

& G 070 726

Ford: WSS-M2C200-D2 & M2C200-D3

PSA: 9730A8, B71 2316 & Special PSA Fluid Part No 1618078480



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	B240-001	5020618211112
5 Litre	B240-005	5020618211129
20 Litre	B240-020	5020618211136

Product Benefits

- * Latest technology additives ensure positive and problem free gear selection
- * Exceptionally good high temperature stability ensuring maximum protection

Product Usage

Use as per vehicle manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com



PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

HD 75W GL-4

1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	7	<11	10.01
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			56.91
Density	ASTM D792	@ 15°C			0.85

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.