

TECHNICAL DATA SHEET

Pro Power

75W-80 MTF

1 Litre & 5 Litre

Product Description

Pro Power Ultra 75W-80 MTF is a premium fully synthetic, fuel efficient manual gearbox oil recommended for a variety of highly stressed manual gearboxes found in many cars and vans.

Recommended for use by Pro Power for the following manufacturer's specifications

API: GL-4 & GL-5

PERTS IN HIGH QUALITY OIL

BMW: MTF LT-2, MTF LT-3 & MTF LT-4

Fiat: 9.55550-MZ1 & 9.55550-MZ6

Ford: WSD-M2C200-C & WSS-M2C200-D2

GM: 1940182, 1940764, 1940768, 1940004 & 19529104 Honda: Special MTF, Special MTF-II & Special MTF III

PSA: B71 2330

Volvo: 97308 & 97309

VW: G 052 178, G 052 512, G 052 726, G 060 726, G 009 317, G 052 171, G 052 527-A2, G 50 & G 70 726 A2

Nissan: MT-XZ & MT-XZ (JR Type)



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	B320-001	5020618211143
5 Litre	B320-005	5020618211150

Product Benefits

- * Latest technology additives ensure positive and problem free gear selection
- * Excellent cold start fluidity ensuring fast circulation
- * Exceptionally good high temperature stability ensuring maximum protection

Product Usage

Use as per vehicle manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power

75W-80 MTF

1 Litre & 5 Litre

Shelf Life

EXPERTS IN HIGH QUALITY OIL

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	7	<11	10.01
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			56.91
Density	ASTM D792	@ 15°c			0.85

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024