

## **TECHNICAL DATA SHEET**

#### **Pro Power**

### **Auto DII**

1 Litre, 5 Litre & 20 Litre

#### **Product Description**

Pro Power Ultra Auto D II is a mineral auto transmission fluid (ATF) for use in many modern automatic transmissions. Manufactured using highly refined oils and high performance additives.

# Recommended for use by Pro Power for the following manufacturer's specifications

Allison: C4 CAT: TO-2

PERTS IN HIGH QUALITY OIL

Ford: Mercon®, WSS-M2C166-H & WSS-M2C138-CJ

MB: 236.7 & 236.1

ZF: TE-ML-09, TE-ML-11 & TE-ML-14

GM: Dexron II-D

#### **Product Benefits**

- \* Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts
- \* Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties
- Outstanding low temperature fluidity



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	C300-001	5020618211174
5 Litre	C300-005	5020618211181
20 Litre	C300-020	5020618211198

#### **Product Usage**

Use as per vehicle manufacturers recommendations.

#### **Storage Instructions**

Store sealed and upright in a cool dry place & out of the reach of children.

#### **Shelf Life**

5 Years from date of manufacture.

Appearance : Red liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil Revision: 2 | Date: 20/01/2025



## **TECHNICAL DATA SHEET**

### **Pro Power**

## **Auto DII**

1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s			8.07
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			43.59
Density	ASTM D792	@ 15°c			0.864

#### **Safety Precautions**

**EXPERTS IN HIGH QUALITY OIL** 

Please see our latest EC Safety Data Sheets for details.

#### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 2 | Date: 20/01/2025