

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto D III

1 Litre, 5 Litre & 20 Litre

Product Description

Pro Power Ultra Auto D III is a premium semi synthetic auto transmission fluid (ATF) for use in many modern automatic transmissions. Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts.

Recommended for use by Pro Power for the following manufacturer's specifications

Allison: C4 & TES-389

Ford: Mercon®

MB: 236.10, 236.5, 236.6, 236.7, 236.9, 236.1 & 236.8

Volvo: 97341 & 97340

CAT: TO-2

ZF: TE-ML-03D, TE-ML-04D, TE-ML-09, TE-ML-14B, TE-ML-16L, TE-ML-17C, TE-ML-02F, TE-ML-11A, TE-ML-11B & TE-ML-14A

GM: Dexron III H

MAN: 339 V1, 339 V2, 339 Z1, 339 Z2 & 339F

Voith: 55.6335 (G607)



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	C315-001	5020618211204
5 Litre	C315-005	5020618211211
20 Litre	C315-020	5020618211228

Product Benefits

- * Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties
- * Outstanding low temperature fluidity
- * Can be used where a Dexron II product is specified

Product Usage

Use as per vehicle manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto D III

1 Litre, 5 Litre & 20 Litre

Shelf Life

5 Years from date of manufacture.

Appearance	:	Red liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm²/s			7.55
Viscosity, Kinematic 40°C	ASTM D445	mm²/s			37.26
Density	ASTM D792	@ 15°C			0.848

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com