

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto D VI 1 Litre & 5 Litre

Product Description

Pro Power Ultra Auto D VI is a premium fully synthetic auto transmission fluid (ATF) for use in many modern automatic transmissions providing a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties.



Size	Part No	Barcode
1 Litre	C320-001	5020618211235
5 Litre	C320-005	5020618211242

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto D VI 1 Litre & 5 Litre

Recommended for use by Pro Power for the following manufacturer's specifications

Allison: C4

CAT: TO-2

Ford: Mercon® SP, Mercon® V, WSS-M2C924-C, Mercon®, WSS-M2C166-H, WSS-M2C195-A, WSS-M2C202-B, WSS-M2C938-A & Mercon® LV

GM: Dexron VI, Dexron II-D, Dexron III H, Dexron III G & Dexron TASA

JASO: 1-A

MB: 236.10, 236.12, 236.14, 236.17, 236.41, 236.5, 236.1, 236.6, 236.7, 236.8, 236.9 & ZF HP20

Voith: 55.6335 (G607)

Volvo: 97340

ZF: TE-ML-09, 5 HP 18FL, 5 HP 19FL & 5 HP 24A

Toyota: T-IV, Type T-III & WS

Aisin Warner: AW-1

Honda: DW-1

JWS: 3309 & 3324

Nissan: Matic D, Matic J, Matic K & Matic S

Texaco: ETL-8072B & 7045-E

Esso: LT71141ATF

VW: G 055 025-A2, G 052 162-A1 & G 052 162-A2

BMW: ETL-7045, ETL-8072B & LA2634

BMW/Mini: JWS 3309 NAG 1

Daewoo: LT71141

Fiat: Typo T-IV

Honda/Acura: Premium & Z1

Hyundai/Kia: SP II, SP III, SP IV & SPH-IV

Isuzu Besco: ATF II & ATF III

Jaguar: ATF 3403 M115, JLM 20238 & LT 71141

Mazda: ATF M-III

Mitsubishi: Diamond SP-II, Diamond SP-III & Diamond SP-IV

Porsche: ATF 3403-M115

Subaru: ATF & ATF-HP

Suzuki: ATF 3309

Product Benefits

- * Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts
- * Outstanding low temperature fluidity
- * Can be used where Dexron II and Dexron III products are specified

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto D VI 1 Litre & 5 Litre

Product Usage

Use as per vehicle manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance	:	Red liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	4.5	6.4	6.2
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s		32	
Viscosity, CCS	ASTM D4684	mPa.s		3200	

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*