

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro Power Auto MV

1 Litre, 5 Litre & 20 Litre

#### Product Description

Pro Power Ultra Auto MV is a next generation fully synthetic auto transmission fluid (ATF) designed for anti-shudder performance in modern transmissions. Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts

#### Recommended for use by Pro Power for the following manufacturer's specifications

Allison: C4 & TES-295

Ford: Mercon®, Mercon® V, WSS-M2C166-H, WSS-M2C195-A, WSS-M2C202-B & WSS-M2C924-C

GM: Dexron III H & 93160393

JASO: 1-A

MAN: 339 V1, 339 Z1 & 339 Z2

MB: 236.3, 236.5, 236.6, 236.7 & 236.9

Voith: 55.6335 (G607)

Volvo: 97340, 97341 & 11 61 540-8

ZF: TE-ML-03D, TE-ML-04D, TE-ML-14A, TE-ML-14B, TE-ML-16L & TE-ML-17C

ATF: SPII, SPIII & Type A, Suffix A (TASA)

Esso: LT71141ATF

Idemitsu: K17

JWS: 3309

Mopar: ATF+3 & ATF+4

Nissan: Matic J & Matic K

Saab: 3309 & 93 165 147

Texaco: ETL-8072B & N402

Toyota: T-IV

VW: G 052 990-A2 & G 055 025-A2



Size	Part No	Barcode
1 Litre	C325-001	5020618211259
5 Litre	C325-005	5020618211266
20 Litre	C325-020	5020618211273

#### Product Benefits

- \* Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties
- \* Outstanding low temperature fluidity
- \* Exceeds the requirements of over 75 Asian, European and American motor manufacturers

Revision: 2 | Date: 20/01/2025

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

**Pro Power**

**Auto MV**

1 Litre, 5 Litre & 20 Litre

### Product Usage

Use as per vehicle manufacturers recommendations.

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

### Shelf Life

5 Years from date of manufacture.

Appearance	:	Red liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			38.35
Density	ASTM D792	@ 15°C			0.848
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s			7.291

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 2 | Date: 20/01/2025

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*