

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto CVT 1 Litre & 5 Litre

Product Description

Pro Power Ultra Auto CVT is a fully synthetic fluid suitable for belt or chain driven continuously variable transmissions (CVT). Pro Power Ultra Auto CVT should NOT be used in conventional stepped automatic transmissions, DCT (Dual Clutch Transmissions), manual transmissions or Toyota e-CVT (THS, Toyota Hybrid System)

Recommended for use by Pro Power for the following manufacturer's specifications

Honda: HMMF & HCF-2
Hyundai/Kia: SP CVT-1
Mazda: CVTF 3320
MB: 236.20 & CVT 28
Mini: EZL 799 & EZL 799A
Nissan: NS-1, NS-2, NS-2V & NS-3
Suzuki: CVT Green 1, NS-2, CVTF 3320 & TC
Toyota: TC & CVTF FE
VW: G 052 516, TL 521 80, G 052 180-A1, G 052 180-A2, G 052 180-A6 & TL 521 16
BMW: 83220136376 & 83220429154
Renault: Elfmatic
Subaru: CV-30, E-CVTF, I-CVTF, K0425Y0710 & Lineartronic-CVTF
Ford: CVT23, M2C933-A, Mercon® C, WSS-M2C928-A, CFT23 & CFT30
Jeep: NS-2 & CVTF+4
Mitsubishi: CVTF-J1
BMW/Mini: ZF CVT V1
GM: Dex-CVT
Mopar: CVT 4



Size	Part No	Barcode
1 Litre	C335-001	5020618211327
5 Litre	C335-005	5020618211334

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto CVT 1 Litre & 5 Litre

Product Benefits

- * Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts
- * Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties
- * Outstanding low temperature fluidity

Product Usage

Use as per vehicle manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance	:	Red liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.5	8.5	7.5
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			35

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com



PRO+POWER **ULTRA**

TECHNICAL DATA SHEET

Pro Power
Auto CVT
1 Litre & 5 Litre

Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025



For further information visit www.propoweroil.com