

TECHNICAL DATA SHEET

Pro Power

ISO 32

20 Litre & 199 Litre

Product Description

Pro Power Ultra ISO 32 is a premium grade mineral based hydraulic oil with excellent anti-wear properties to give maximum protection in the most demanding of systems whilst controlling rust, corrosion and oxidation.

Recommended for use by Pro Power for the following manufacturer's specifications

Afnor: NFE E 48-600

Denison Filterability: TP02100

Denison: HF-2

PERTS IN HIGH QUALITY OIL

DIN: 51524 Part 2 (HLP)

ISO: 6743-4 SEB: 181.222

Sperry Vickers: I-286-S & M-2950-S

Thyssen: TH N-256132

US Steel: 127 VDMA: 24318



* Image for illustrative purposes only.

Size	Part No	Barcode		
20 Litre	E225-020	5020618211419		
199 Litre	E225-199	5020618211426		

Product Benefits

- * Anti-foam additive to control foam and assist with the quick release of air
- * Suitable for a wide range of hydraulic systems and applications
- * Not suitable for systems in which silver-plated components are used

Product Usage

Use as per the component manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power

ISO 32

20 Litre & 199 Litre

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°c	ASTM D445	mm²/s	28.8	35.2	32.4
Viscosity, Kinematic 100°c	ASTM D445	mm²/s			5.8
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				120

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024