

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

ISO 68

20 Litre

Product Description

Pro Power Ultra ISO 68 is a premium grade mineral based hydraulic oil with excellent anti-wear properties to give maximum protection in the most demanding of systems whilst controlling rust, corrosion and oxidation.

Recommended for use by Pro Power for the following manufacturer's specifications

Afnor: NFE E 48-600
Denison Filterability: TP02100
Denison: HF-2
DIN: 51524 Part 2 (HLP)
ISO: 6743-4
SEB: 181.222
Sperry Vickers: I-286-S & M-2950-S
Thyssen: TH N-256132
US Steel: 127
VDMA: 24318



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	E227-020	5020618211440

Product Benefits

- * Anti-foam additive to control foam and assist with the quick release of air
- * Suitable for a wide range of hydraulic systems and applications
- * Not suitable for systems in which silver-plated components are used

Product Usage

Use as per the component manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid
Odour : Characteristic

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

ISO 68

20 Litre

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	61.2	74.8	67.64
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s			8.79
Density	ASTM D792	@ 15°C			0.874

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com