

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro Power 10W-30 AGRI 20 Litre

#### Product Description

Pro Power Ultra 10W-30 AGRI has been formulated with the latest additive technology and high quality base oils to produce a universal lubricant for tractors, combines and agricultural machinery operating in the severest of conditions. Suitable for use in certain final drives, hydraulic systems, wet brakes, transmission and engines.

#### Recommended for use by Pro Power for the following manufacturer's specifications

Ford: WSS-M2C159B, WSS-M2C159C, WSS-M2C134-D & WSS-M2C86-B

John Deere: JDM J27 & JDM 20C

Massey Ferguson: M1144, M1145 & M1143

New Holland: 82009201, 030C, 410-B & 420-A

ZF: TE-ML-03A, TE-ML-06B, TE-ML-07B & TE-ML-07D

ACEA: E3

Allison: C4

API: CE/SF, CF, CF-4, CG-4 & GL-4

CAT: TO-2

MB: 227.1

MIL: MIL-L-2104 D

Afnor: NFE 65603 E

Case New Holland: MAT3525

CCMC: D4



\* Image for illustrative purposes only.

| Size     | Part No  | Barcode       |
|----------|----------|---------------|
| 20 Litre | F100-020 | 5020618211457 |

#### Product Benefits

- \* High performance additives give precise clutch and brake operation
- \* Superior wear, rust and corrosion protection
- \* Specially selected additives helps to preserve seals and stops leaks

#### Product Usage

Use as per the component manufacturers recommendations.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

**Pro Power**  
**10W-30 AGRI**  
20 Litre

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

### Shelf Life

5 Years from date of manufacture.

|                         |   |                    |
|-------------------------|---|--------------------|
| Appearance              | : | Amber liquid       |
| Odour                   | : | Characteristic     |
| Solubility              | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil                |

| Test                       | Method     | Unit               | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445  | mm <sup>2</sup> /s | 9.3  | 12.5 |         |
| Viscosity, CCS             | ASTM D4684 | mPa.s              |      | 7000 |         |
| Pour Point                 | ASTM D97   | °C                 |      | -30  |         |
| HTHS Viscosity             | ASTM D4683 | mPa.s              | 2.9  |      |         |

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*