

TECHNICAL DATA SHEET

Pro Power

Red Antifreeze & Summer Coolant

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra Red Antifreeze & Summer Coolant is a longlife winter antifreeze and summer coolant, giving up to 5 years of protection. May be used where Glysantin® G12, G12+, G30, G33 or G34 products were originally recommended. Uses OAT - Organic Acid Inhibitor Technology.

Recommended for use by Pro Power for the following manufacturer's specifications

AFNOR: NF R15-601 ASTM: D3306 & D4985

BS: 6580:2010 CUNA: NC 956-16

EXPERTS IN HIGH QUALITY OIL

SAE: J1034 UNE: 26361-88 FFV HEFT: R443 JIS: K 2234 NATO: S 759



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	X565-001	5020618211471
5 Litre	X565-005	5020618211549
20 Litre	X565-020	5020618211488
199 Litre	X565-199	5020618211495

Product Benefits

- * Protects against corrosion, overheating and freezing
- * Includes a bittering agent to help prevent accidental swallowing of the product

Product Usage

Use as per the component manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Revision: 4 | Date: 15/09/2025



TECHNICAL DATA SHEET

Pro Power

Red Antifreeze & Summer Coolant

1 Litre, 5 Litre, 20 Litre & 199 Litre

Specification Information

Freeze Protection:

EXPERTS IN HIGH QUALITY OIL

-38°C freeze protection- dilute @ 80% Antifreeze to 20% water.

-20°C freeze protection- dilute @ 50% Antifreeze to 50% water.

Appearance : Pink/Red liquid

Odour : Odourless

Solubility : Miscible in water

Test	Method	Unit	Min.	Max.	Typical
Density	ASTM D792	@ 15°c			1.091
Freezing Point		°C		-22	

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 4 | Date: 15/09/2025