

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro+Power Ultra 10W-60 SPORT 5 Litre

Product Description

Pro Power Ultra 10W-60 SPORT is a fully synthetic engine oil with the latest additive technology available, providing an oil with outstanding performance and durability for the most demanding motorist. Designed to cope with the high operating temperatures encountered in high performance engines and its modern additive chemistry provides stay-in-grade characteristics for extended periods.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A3/B3 & A3/B4
API: SN/CF

Product Benefits

- * High film strength provides superior engine protection
- * Low volatility greatly reduces oil consumption
- * Excellent anti-wear protection
- * Outstanding thermal stability at elevated temperatures

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

| | | |
|-------------------------|---|--------------------|
| Appearance | : | Amber liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil |



* Image for illustrative purposes only.

| Size | Part No | Barcode |
|---------|----------|---------------|
| 5 Litre | A484-005 | 5020618210979 |

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro+Power Ultra 10W-60 SPORT 5 Litre

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 21.9 | <26.1 | 24.396 |
| Viscosity, CCS | ASTM D4684 | mPa.s | | 7000 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 10 | | 10.625 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.7 | | |
| NOACK Volatility | ASTM D5800 | % | | 13 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 168.124 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |
| Pour Point | ASTM D97 | °C | | -30 | |

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com