

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro+Power Ultra 10W-50 RACING 1 Litre & 5 Litre

#### Product Description

Pro Power Ultra 10W-50 RACING is a premium fully synthetic engine oil utilising the latest synthetic technology designed for use in high powered, multi valve engines with natural aspiration or turbocharged.

Recommended for use by Pro Power for the following manufacturer's specifications

API: SN  
ACEA: A3/B4

#### Product Benefits

- \* Latest synthetic technology motor oil
- \* Excellent anti-wear protection at high temperatures
- \* High film strength provides superior engine protection
- \* Outstanding thermal stability at elevated temperatures

#### Product Usage

Use as per engine manufacturers recommendations.

#### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

#### Shelf Life

5 Years from date of manufacture.

|                         |   |                    |
|-------------------------|---|--------------------|
| Appearance              | : | Amber liquid       |
| Odour                   | : | Characteristic     |
| Solubility              | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil                |



\* Image for illustrative purposes only.

| Size    | Part No  | Barcode       |
|---------|----------|---------------|
| 1 Litre | A490-001 | 5020618211563 |
| 5 Litre | A490-005 | 5020618211570 |

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 22/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro+Power Ultra 10W-50 RACING 1 Litre & 5 Litre

| Test                       | Method     | Unit               | Min.  | Max. | Typical |
|----------------------------|------------|--------------------|-------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445  | mm <sup>2</sup> /s | >16.3 | 21.9 | 19.1    |
| Viscosity, Kinematic 40°C  | ASTM D445  | mm <sup>2</sup> /s |       |      | 128     |
| Density                    | ASTM D792  | @ 15°C             |       |      | 0.851   |
| Total Base Number          | ASTM D2896 | mg KOH/g           | >10   |      |         |
| Pour Point                 | ASTM D97   | °C                 |       | -30  |         |
| HTHS Viscosity             | ASTM D4683 | mPa.s              | 3.7   |      |         |
| NOACK Volatility           | ASTM D5800 | %                  |       | 13   |         |
| Viscosity, CCS             | ASTM D4684 | mPa.s              |       | 7000 |         |

#### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

#### Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 22/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)