

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro Power 75W-90 Total Drive Line 1 Litre

#### Product Description

Pro Power Ultra 75W-90 Total Drive Line is a universal synthetic transmission oil for the total drive line, it is a heavy duty, multipurpose, long life gear oil recommended for use in a wide range of cars and vans.

#### Recommended for use by Pro Power for the following manufacturer's specifications

API: GL-4, GL-5 & MT-1

MAN: 341 Type Z-2, 341 Type E-3 & 342 Type M3

SAE: J2360

Scania: STO 1.0, STO 1.1 G & STO 2.0 A FS

ZF: TE-ML-02B, TE-ML-07A, TE-ML-08, TE-ML-17B, TE-ML-21A, TE-ML-05B, TE-ML-12B, TE-ML-12L, TE-ML-12N, TE-ML-13 & TE-ML-19C

Arvin Meritor: 0-76-N

Detroit Fluids: DFS 93K219.01

Iveco: Extended Drain

Mack: GO-J Plus

MB: 235.8

MIL: MIL-PRF-2105E

Volvo: 97312



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	B305-001	5020618211587

#### Product Benefits

- \* Premium fully synthetic, heavy duty, multipurpose, long life gear oil for use in many modern vehicles
- \* Contains highly effective extreme pressure and anti-wear additives
- \* Recommended for a variety of highly stressed manual gearboxes, heavily loaded axle drives, transfer boxes and other transmission equipment
- \* Exceptionally good high temperature stability ensuring maximum protection

#### Product Usage

Use as per engine manufacturers recommendations.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 22/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

Pro Power

75W-90 Total Drive Line

1 Litre

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

### Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	13.5	<18.5	15.6
Viscosity, Kinematic 40°C	ASTM D445	mm²/s			80.8
Density	ASTM D792	@ 15°C			0.862

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 22/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*