

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro+Power Ultra 5W-30 C3 ST 1 Litre & 5 Litre

Product Description

Pro Power 5W-30 C3 ST is a fully Synthetic engine oil specially formulated for certain Stellantis group DV5R & EB2 engine types. The product helps prevent occurrences of LSPI

(Low Speed Pre-Ignition) whilst offering excellent engine protection and emission control. Please check which oil is recommended for the engine type prior to use.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C3
API: SN Plus
GM: Dexos™ 2
MB: 229.31, 229.51 & 229.52
Stellantis: FPW9.55535/03 (V1)
PSA: B71 2290 & B71 2297

Product Benefits

- * Excellent Engine Protection
- * Reduces occurrences of LSPI
- * Outstanding emission Control

Product Usage

Use as per engine manufacturers recommendations

Directions for Use

As per the vehicle handbook

Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children



* Image for illustrative purposes only.

| Size | Part No | Barcode |
|---------|----------|---------------|
| 1 Litre | A336-001 | 5020618211754 |
| 5 Litre | A336-005 | 5020618211761 |

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro+Power Ultra
5W-30 C3 ST
1 Litre & 5 Litre

Shelf Life

5 years from date of manufacture

| | | |
|-------------------------|---|--------------------|
| Appearance | : | Amber liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 11 | 12.5 | 12.2 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |
| Viscosity, CCS | ASTM D4684 | mPa.s | | 6600 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 6 | | 9.5 |
| Pour Point | ASTM D97 | °C | -36 | | |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.5 | | |
| NOACK Volatility | ASTM D5800 | % | | 9 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | 65 | | 72.9 |
| Viscosity Index | ASTM D2270 | | | | 166 |

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 26/03/2025

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*