

PRO+POWER ULTRA

Technical Data Sheet

Pro Power Ultra 5W-30 C3 VW



Product details :

Pro Power Ultra 5W-30 C3 VW is a fully synthetic low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engines, and designed to give maximum protection to diesel particulate filters (DPF)

- Premium motor oil recommended for many modern vehicles, including those from Audi, VW, Skoda, Seat, BMW, Mercedes-Benz, Porsche and others
- Suitable for long life service intervals
- Latest synthetic technology motor oil
- Formulated to give excellent fuel efficiency
- Protects sensitive exhaust after-treatment devices, such as DPF's - diesel particulate filters

Recommended for use in vehicles requiring :

- ACEA C3
- API SN
- VAG Group VW 504.00/507.00
- BMW LL-04
- Mercedes-Benz 229.5
- Porsche C30

Part numbers :

| | |
|----------|------------------|
| A331-001 | 1ltr |
| A331-005 | 5ltr |
| A331-020 | 20ltr |
| A331-199 | 199ltr |
| A331-IBC | IBC - 1,000ltr |
| A331-BLK | Bulk from 500ltr |

Typical test data :

| | |
|-----------------------------------|------|
| Kinematic Viscosity @ 100°C (cSt) | 11.8 |
| Kinematic Viscosity @ 40°C (cSt) | 72.3 |
| Viscosity index | 160 |
| CCS @ -30°C (cP) | 6080 |
| Sulphated Ash (% w/w) | 0.60 |
| Flash Point COC (°C) | 212 |
| TBN (mg KOH / g) | 6.00 |

For further information visit www.propoweroil.com