

PRO+POWER ULTRA

Technical Data Sheet

Pro Power Ultra C2 C3 PLUS



Product details :

Pro Power Ultra 5W-30 C2 / C3 PLUS is a fully synthetic low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engines, designed to give maximum protection to diesel particulate filters (DPF).

- Premium motor oil recommended for many modern vehicles, including those from Vauxhall, Mercedes-Benz, Peugeot/Citroen and others
- Suitable for long life service intervals
- Latest synthetic technology motor oil
- Formulated to give excellent fuel efficiency
- Protects sensitive exhaust after-treatment devices, such as DPF's - diesel particulate filters

Recommended for use in vehicles requiring :

- ACEA C2, C3
- API SN
- General Motors dexos2™
- Mercedes-Benz 229.52, 229.51, 229.31
- PSA B71 2290 (pre-2017)

Part numbers :

A333-001	1ltr
A333-005	5ltr
A333-020	20ltr
A333-199	199ltr
A333-IBC	IBC - 1,000ltr
A333-BLK	Bulk from 500ltr

Typical test data :

Kinematic Viscosity @ 100°C (cSt)	12.3
Kinematic Viscosity @ 40°C (cSt)	73.1
Viscosity Index	167
Density @ 15°C	0.852
Flash Point, COC (°C)	230
TBN (mg KOH/g)	7.5
Cold Cranking Viscosity @ -30°C (cP)	5650

For further information visit www.propoweroil.com