

PRO+POWER ULTRA

Technical Data Sheet

Pro Power Ultra 15W-40 E7



Product details :

Pro Power Ultra 15W-40 E7 is a true multi fleet engine oil, ideal for use in truck, bus, coach, van and certain automotive vehicles

- Suitable for use in petrol and diesel engines including turbo and non-turbocharged
- Premium additives to help control soot and sludge levels in the oil
- Extended drain intervals are possible, check vehicle manufacturers recommendations
- Can be used in Euro 3, 4 & certain Euro 5 engines, check vehicle manufacturer's requirements

Recommended for use in vehicles requiring :

- See page 2 for details

Part numbers :

D100-020	20ltr
D100-199	199ltr
D100-IBC	IBC - 1,000ltr
D100-BLK	Bulk from 500ltr

Typical test data :

Specific Gravity @ 15.5°C	0.887
Kinematic Viscosity @ 100°C (cSt)	14.6
Kinematic Viscosity @ 40°C (cSt)	110.0
Viscosity Index	137
TBN (mg KOH/g)	10.2
Pour Point (°C)	-35
Flash Point (°C)	226

For further information visit www.propoweroil.com

PRO+POWER

ULTRA

Technical Data Sheet

Pro Power Ultra 15W-40 E7 is recommended for use in vehicles requiring :

API	CI-4/SL, CF
ACEA	E7, A3/B3, A3/B4
Mercedes Benz	228.3, 229.1
Cummins	CES 20078, 20071/72/76/77
MAN	M3275
MTU	Type 2
Mack	EO-N, EO-M Plus
Volvo	VDS-3
Renault	RVI RLD-2, RLD
Global	DHD-1
ZF	TE-ML 04C / 07C
Caterpillar	ECF-2, ECF-1-a
Allison	C4
Detroit Diesel	DDC 93K215
JASO	DH-1
Deutz	DQC III-10

For further information visit www.propoweroil.com