

PRO+POWER ULTRA

Technical Data Sheet

Pro Power Ultra ISO 68



Product details :

Pro Power Ultra ISO 68 is a premium grade mineral based hydraulic oil with excellent anti-wear properties to give maximum protection in the most demanding of systems

- Premium additives to control rust, corrosion and oxidation
- Anti-foam additive to control foam and assist with the quick release of air
- Suitable for a wide range of hydraulic systems and applications
- Not suitable for systems in which silver-plated components are used

Recommended for use in vehicles requiring :

- DIN 51524 Part 2, category HLP
- ISO 6743/4, category HM
- Denison HF-2
- TP-02100 Filterability Test
- Sperry Vickers M-2950-S, I-286-S
- Afnor NF E 48-600
- Thyssen TH N-256132
- US Steel 127
- SEB 181.222
- VDMA 24318

Part numbers :

E227-020	20ltr
E227-199	199ltr
E227-IBC	IBC - 1,000ltr
E227-BLK	Bulk from 500ltr

Typical test data :

Specific Gravity @ 15.6°C	0.880
Kinematic Viscosity @ 40°C (cSt)	68.0
Kinematic Viscosity @ 100°C (cSt)	8.75
Viscosity Index	100
Flash Point (COC °C)	224
Pour Point (°C)	-31

For further information visit www.propoweroil.com