

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Product name	: Longlife Antifreeze & Coolant - Yellow
UFI	: AS5C-50GY-X007-53M1
Product code	: X731
Product group	: Trade product

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: For professional use only Industrial
Use of the substance/mixture	: Anti-freezing agents
Function or use category	: Anti-freezing agents

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****Supplier**

Rapid Group  
Alexandra House  
Winchester Hill  
SO51 7ND Romsey - UK  
[www.propoweroil.com](http://www.propoweroil.com)

**1.4. Emergency telephone number**

Emergency number	: 03333 445955 Office Hours (08.30 - 17.00)
------------------	--

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Acute toxicity (oral), Category 4	H302
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Repeated exposure, Category 2	H373
Full text of H statements : see section 16	

**Adverse physicochemical, human health and environmental effects**

May cause damage to organs through prolonged or repeated exposure. Harmful if swallowed. Causes serious eye irritation.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



GHS07

GHS08

Signal word (CLP)

: Warning

# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H302 - Harmful if swallowed. H319 - Causes serious eye irritation. H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P264 - Wash hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P301+P312 - IF SWALLOWED: Call a POISON CENTER, doctor if you feel unwell. P330 - Rinse mouth. P260 - Do not breathe vapours, spray. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanediol; ethylene glycol substance with a Community workplace exposure limit	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119456816-28	≥ 80 – < 90	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
2,2' -oxybisethanol; diethylene glycol	(CAS-No.) 111-46-6 (EC-No.) 203-872-2 (EC Index-No.) 603-140-00-6	≥ 7.5 – < 10	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
POTASSIUM 2-ETHYL HEXANOATE	(CAS-No.) 3164-85-0 (EC-No.) 221-625-7 (REACH-no) 01-2119980714-29	≥ 1 – < 2.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact	: Eye irritation.
------------------------------------	-------------------

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

#### 7.3. Specific end use(s)

No additional information available

# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

ethanediol; ethylene glycol (107-21-1)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Ethylene glycol
IOEL TWA	52 mg/m <sup>3</sup>
IOEL TWA [ppm]	20 ppm
IOEL STEL	104 mg/m <sup>3</sup>
IOEL STEL [ppm]	40 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethane-1,2-diol
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> particulate 52 mg/m <sup>3</sup> vapour
WEL TWA (OEL TWA) [2]	20 ppm vapour
WEL STEL (OEL STEL)	104 mg/m <sup>3</sup> vapour
WEL STEL (OEL STEL) [ppm]	40 ppm vapour
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

##### 2,2'-oxybisethanol; diethylene glycol (111-46-6)

United Kingdom - Occupational Exposure Limits	
Local name	2,2'-Oxydiethanol
WEL TWA (OEL TWA) [1]	101 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	23 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

#### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

#### 8.2.2.3. Respiratory protection

**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: odourless.
Odour threshold	: No data available
pH	: 7.5 – 9
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -12 °C
Freezing point	: No data available
Boiling point	: > 170 °C
Flash point	: > 111 °C
Auto-ignition temperature	: > 400 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 0.06 mm Hg @ 20 deg C
Relative vapour density at 20 °C	: 2.1 (Air = 1.0)
Relative density	: 1.11 @ 20 deg C
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Explosive limits : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Longlife Antifreeze & Coolant - Yellow

ATE CLP (oral)	540.541 mg/kg bodyweight
----------------	--------------------------

Skin corrosion/irritation : Not classified  
pH: 7.5 – 9

Serious eye damage/irritation : Causes serious eye irritation.  
pH: 7.5 – 9

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

#### ethanediol; ethylene glycol (107-21-1)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2,2' -oxybisethanol; diethylene glycol (111-46-6)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified  
Not rapidly degradable

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN -	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.5. Environmental hazards

Dangerous for the environment : No	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

No data available

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration



# Longlife Antifreeze & Coolant - Yellow

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.