

# PRO+POWER ULTRA

## Technical Data Sheet Pro Power Ultra Auto DIII

### Product details :

Pro Power Ultra Auto D III is a premium semi synthetic auto transmission fluid (ATF) for use in a many modern automatic transmissions



- Premium semi synthetic auto transmission fluid (ATF) for use in many modern vehicles
- Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts
- Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & antiwear properties
- Outstanding low temperature fluidity
- Can be used where a Dexron II product is specified

### Product specifications :

- GM DEXRON IIIH
- Ford MERCON
- Voith 55.6335 (G607)
- Allison C-4, TES-389
- Volvo 97341, 97340
- Mercedes-Benz 236.10, 236.9, 236.8, 236.7, 236.6, 236.5, 236.1
- ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 14B, 16L, 17C
- Caterpillar TO-2
- MAN 339F, 339 V1 & Z1, 339 V2 & Z2

### Part numbers :

C315-001	1ltr
C315-005	5ltr
C315-020	20ltr
C315-199	199ltr
C315-IBC	IBC - 1,000ltr
C315-BLK	Bulk from 500ltr

### Typical test data :

Appearance	Red
Density @ 15.6°C	0.882
Kinematic Viscosity @ 100°C (cSt)	7.91
Flash Point COC (°C)	205
Pour Point (°C)	-53

For further information visit [www.propoweroil.com](http://www.propoweroil.com)