

PRO+POWER ULTRA

Technical Data Sheet

Pro Power Ultra Auto DCT **Product details :**

Pro Power Ultra Auto DCT is a fully synthetic fluid suitable for a wide range of vehicles fitted with DSG or DCT auto transmissions



- Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts
- Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & antiwear properties
- Outstanding low temperature fluidity

Product specifications :

- VAG Group G 052 182 A2, G 052 529 A2
- Porsche 999.917.080.00, 000.043.207.29, 000.043.207.30
- BMW 83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214 (DCTF-1), 83 22 2 147 477
- Peugeot/Citroën 9734.S2
- Ford M2C936-A
- Mercedes-Benz 236.21, 236.25
- Mitsubishi MZ320065 DIA-QUEEN SSTF-I
- Volvo 1161838, 1161839
- (See page 2 for additional details)

Part numbers :

C330-001	1ltr
C330-005	5ltr
C330-020	20ltr
C330-199	199ltr
C330-IBC	IBC - 1,000ltr
C330-BLK	Bulk from 500ltr

Typical test data :

Appearance	Amber fluid
Density @ 15.6°C	0.845
Kinematic Viscosity @ 100°C (cSt)	6.96
Brookfield Viscosity @ -40°C (cP)	12,280
Flash Point COC (°C)	200
Pour Point (°C)	- 45°C

For further information visit www.propoweroil.com

PRO+POWER

ULTRA

Technical Data Sheet

Pro Power Ultra Auto DCT is recommended for service fill applications in the vast majority of dual clutch transmission applications on the road today. In particular, Pro Power Ultra Auto DCT can be used in any of the following applications.

OEM	Specification
BMW	83 22 2 148 578
	83 22 2 148 579
	83 22 0 440 214 (DCTF-1)
	83 22 2 147 477
83 22 2 167 666 (MTF LT-5)	
Chrysler	68044345 EA & GA
Ferrari	TF DCT-F3
Ford	WSS-M2C936-A
Mercedes-Benz	MB 236.21 (001 989 85 03)
	MB 236.25 (001 989 86 03)
	MB 236.24
Mitsubishi	MZ320065 Dia-Queen SSTF-I
Porsche	Oil No. 999.917.080.00
	Oil No. 000.043.207.29
	Oil No. 000.043.207.30
PSA	9734.S2
Renault	EDC-6
	EDC-7
VAG Group	TL 521 82 / G 052 182 A2, G 052 182 A6
	TL 525 29 / G 052 529 A2, G 052 529 A6
	VW G 055 529
Volvo	1161838, 1161839

In addition, Pro Power Ultra DCT can be used for service fill applications where any of the following fluids were originally specified: Castrol BOT 341, Castrol BOT 450, Castrol Transmax Dual, Pentosin FFL 2, Pentosin FFL 3, Pentosin FFL 4, Pentosin FFL 52529, Shell TF DCT -F3.

For further information visit www.propoweroil.com