

PRO+POWER ULTRA

Technical Data Sheet

Pro Power Ultra MV CHF



Product details :

Pro Power Ultra MV CHF is a fully synthetic fluid for use in hydraulic applications including power steering units, shock absorbers, hydro-pneumatic suspensions and traction control systems

- Can be used in convertible roof mechanisms
- Premium synthetic fluid, dyed green in colour for easy identification
- **IMPORTANT:** Do not mix with other grades of ATF or Power Steering Fluids

Product specifications :

- See page 2 for details

Part numbers :

E100-001	1ltr
----------	------

Typical test data :

Appearance	Green liquid
Density @ 20°C	0.819
Kinematic Viscosity @ 100°C (cSt)	5.95
Kinematic Viscosity @ 40°C (cSt)	18.7
Viscosity Index	306
Pour Point (°C)	-54

For further information visit www.propoweroil.com

PRO+POWER

ULTRA

Technical Data Sheet

Pro Power Ultra MV CHF is recommended for out of warranty use where any of the following part numbers or specifications are required :

Audi / Volkswagen	G 002 000 A2, TL 52 146.00
Bentley	RH 5000
BMW/Mini	82 11 1 468 041, 82 11 0 148 132, 83 29 0 429 576
Fendt	X 902 011 622
Ford	WSS-M2C204-A
GM / Opel	Suitable for use
Jeep	Suitable for use
MAN	M3289
Mercedes-Benz	001 989 24 03 10, 001 989 24 03 12, Q 1 32 0001, MB 345.0
Porsche	000 043 203 33
Saab	3032 380
Volvo	11 61 529
ZF	TE-ML 02K
DIN	51524 Part 3
ISO	7308

For further information visit www.propoweroil.com