

# PRO+POWER ULTRA

## Technical Data Sheet

### Pro Power Ultra 5W-30 EURO ECO PLUS



### Product details :

Pro Power Ultra 5W-30 Euro ECO PLUS is a fully synthetic Low SAPS engine oil designed for use in Euro 4, 5 & 6 engines. Suitable for vans, truck, bus, coach, off highway and agricultural applications

- Suitable for use with exhaust gas re-circulation (EGR), selective catalytic reduction (SCR – AdBlue) and diesel particulate filters (DPF)
- Premium additives to help control soot and sludge levels in the oil
- Ideal for use in severe conditions with extended drain intervals
- Not suitable for use in petrol engines

### Recommended for use in vehicles requiring :

- ACEA E4, E7, E8, E11, API CK-4
- Mercedes Benz DTFR 15C120 (MB 228.52), DTFR 15C110 (MB 228.51), DTFR 15C100 (MB 228.31)
- SCANIA LDF-4, LA
- CUMMINS CES 20086, CES 20081
- MAN M3777, M3677
- CATERPILLAR ECF-3
- VOLVO VDS-4.5
- DEUTZ DQC IV-18 LA
- RENAULT TRUCKS RLD-4, RLD-3
- IVECO 18-1804 TLS E6
- JASO DH-2, DH-1, DL-0
- DETROIT DIESEL 93K218, 93K222
- MACK EOS-4.5
- MTU TYPE 3.1, TYPE 2.1

### Part numbers :

D275-020	20ltr
D275-199	199ltr
D275-IBC	IBC - 1,000ltr
D275-BLK	Bulk from 500ltr

### Typical test data :

Density @ 20°C	0.863
Kinematic Viscosity @ 100°C	12.0
Kinematic Viscosity @ 40°C	71.4
Viscosity Index	165
Pour Point (°C)	-42
Flash Point COC (°C)	240
TBN (mg KOH/g)	13.4
Sulphated Ash (% wt)	0.90

For further information visit [www.propoweroil.com](http://www.propoweroil.com)